



RHINO HOIST -TECLES ELÉCTRICOS DE CADENA CON TROLLEY ELECTRICO

Especificaciones Técnicas 0.5 - 50 ton

Model	SSDHL									
	0.5-01S	01-01S	1.5-01S	02-01S	02-02S	2.5-01S	03-01S	03-02S	03-03S	05-02S
Capacity(t)	0.5t	1t	1.5t	2t		2.5t	3t			5t
Lifting speed (m/min)	7.2	6.6	8.8	6.6	3.3	5.4	5.4	4.4	2.2	2.7
Motor power (Kw)	0.8	1.5	3	3	1.5	3	3	3	1.5	3
Rotation speed (r/min)	1440									
Insulation grade	F									
Power supply	3P 220V-380V/220v-440v 60Hz									
Control voltage	24V / 36V / 48V									
No.of chain	1	1	1	1	2	1	1	2	3	2
Spec.of load chain	Φ6.3	Φ7.1	Φ10.0	Φ10.0	Φ7.1	Φ11.2	Φ11.2	10	Φ7.1	Φ11.2
Net weight (kg)	47	61	108	115	73	115	122	131	85	151



Especificaciones Técnicas 10 ton.

Model	SSDHL	
	10-04S	10-04D
Capacity(t)	10t	
Lifting Speed(m/min)	2.7	2.7/0.9
Motor Power(kw)	3.0x2	3.0x2/1.0x2
Rotations Speed(r/min)	1440	2880/960
Insulation Grade	F	
Power Supply	3P 220V 690V	
Control Voltage	24V/36V/48V	
No.of Chain	4	4
Spec.of Load Chain	Φ11.2	
Net Weight(kg)	300	380

Especificaciones Técnicas 15 - 20 ton. De uno y dos velocidades

Model	Capacity	Lifting speed (m/min)	Motor power (kw)	Rotation speed (r/min)	Insulation grade	Power supply	Voltage	No.of chain	Spec. of load chain	Net weight (kg)
15-06S	15t	1.8	3.0x2	1440	F grade	3 phase, 200V-690V, 50/60Hz	24V/36V/48V	6	Φ11.2	382
15-06D	15t	1.8/0.6	3.0x2/1.0x2	2880/960	F grade	3 phase, 200V-690V, 50/60Hz	24V/36V/48V	6	Φ11.2	455
20-08S	20t	1.4	3.0x2	1440	F grade	3 phase, 200V-690V, 50/60Hz	24V/36V/48V	8	Φ11.2	482
20-08D	20t	1.5/0.5	3.0x2/1.0x2	2880/960	F grade	3 phase, 200V-690V, 50/60Hz	24V/36V/48V	8	Φ11.2	545

