



www.rhinolifting.jp



RHINO HOIST
CHAIN HOIST & LIFTING

TECLES ELECTRICOS DE CADENA

RHINO HOIST -TECLES ELÉCTRICOS DE CADENA CON GANCHO DE SUSPENSIÓN

Especificaciones Técnicas 0.5 - 50 ton

Model	SSDHL									
	0.5-01S	01-01S	1.5-01S	02-01S	02-02S	2.5-01S	03-01S	03-02S	03-03S	05-02S
Capacity(t)	0.5t	1t	1.5t	2t		2.5t	3t			5t
Lifting speed (m/min)	7.2	6.6	8.8	6.6	3.3	5.4	5.4	4.4	2.2	2.7
Motor power (Kw)	0.8	1.5	3	3	1.5	3	3	3	1.5	3
Rotation speed (r/min)	1440									
Insulation grade	F									
Power supply	3P 220V/380V - 220V/440V Hz60									
Control voltage	24V / 36V / 48V									
No,of chain	1	1	1	1	2	1	1	2	3	2
Spec.of load chain	Ö6.3	Ö7.1	Ö10.0	Ö10.0	Ö7.1	Ö11.2	Ö11.2	10	Ö7.1	Ö11.2
Net weight (kg)	47	61	108	115	73	115	122	131	85	151

Especificaciones Técnicas 10 ton

Model	SSDHL	
	10-04S	10-04D
Capacity(t)	10t	
Lifting Speed(m/min)	2.7	2.7/0.9
Motor Power(kw)	3.0x2	3.0x2/1.0x2
Rotations Speed(r/min)	1440	2880/960
Insulation Grade	F	
Power Supply	3P 220V 60V	
Control Voltage	24V/36V/48V	
No.of Chain	4	4
Spec.of Load Chain	ö11.2	
Net Weight(kg)	300	380

Cadenas de acero de alta resistencia grado 100.

CONTAMOS CON REPUESTOS ORIGINALES



CONTROL INALAMBRICO



ENSAYOS DE CARGA EN:

CERTIFICACIONES



ABS

